



◆ 主要外形尺寸

公称 口径 DN (mm)	尺寸 (mm)														
	L	H2	H1	1.0Mpa				1.6Mpa				2.5Mpa			
				D	D1	D2	Z-φd	D	D1	D2	Z-φd	D	D1	D2	Z-φd
100	127	285	107	215	180	155	8-18	220	180	156	8-18	235	190	156	8-22
125	140	300	123	245	210	185	8-18	250	210	184	8-18	270	220	184	8-26
150	140	320	140	280	240	210	8-23	285	240	244	8-22	300	250	211	8-26
200	152	370	180	335	295	265	8-23	340	295	266	12-22	360	310	274	12-26
250	165	420	200	390	350	320	12-23	405	355	319	12-26	425	370	330	12-30
300	178	500	250	440	400	368	12-23	460	410	370	12-26	485	430	389	16-30
350	190	530	270	500	460	428	16-23	520	470	429	16-26	555	490	448	16-36
400	216	570	300	565	515	482	16-25	580	525	480	16-30	620	550	503	20-36
450	222	600	320	615	565	532	20-25	640	585	548	20-30	670	600	548	20-36
500	229	680	360	670	620	585	20-25	715	650	609	20-33	730	660	609	20-39
600	267	750	420	780	725	685	20-30	840	770	720	20-36	845	770	720	24-42
700	292	810	480	895	840	800	24-30	910	840	794	24-36	960	875	820	24-48
800	348	905	540	1010	950	905	24-34	1025	950	901	24-39	1085	990	928	28-48
900	330	960	590	1110	1050	1005	28-34	1125	1050	1001	28-39	1185	1090	1028	28-56
1000	410	1010	640	1220	1160	1115	28-36	1255	1170	1112	28-42	1320	1210	1140	32-56
1200	470	1175	750	1450	1380	1325	32-39	1485	1390	1328	32-48	1530	1420	1350	32-56
1400	530	1310	860	1675	1590	1525	36-42	1685	1590	1530	36-48	1755	1640	1560	36-62
1600	600	1460	980	1915	1820	1750	40-48	1930	1820	1750	40-56	1975	1860	1780	40-62
1800	670	1560	1090	2115	2020	1950	44-48	2130	2020	1950	44-56	2195	2070	1985	44-70
2000	760	1670	1190	2325	2230	2160	48-48	2345	2230	2150	48-62	2425	2300	2210	48-70
2200	590	1800	1440	2485	2390	2370	52-48	2560	2445	2370	52-60				
2400	650	1930	1550	2685	2590	2580	56-48	2760	2645	2580	56-60				
2600	700	2280	1660	2930	2820	2790	60-55	3010	2885	2790	60-68				
2800	760	2460	1780	3130	3020	3000	64-55	3210	3085	3000	64-68				
3000	810	2600	1940	3330	3220	3200	68-55	3410	3285	3200	68-68				